

SECTION **PG**

**POWER SUPPLY, GROUND & CIRCUIT ELEMENTS**

**CONTENTS**

<b>PRECAUTION</b> .....	3	Wiring Diagram - ACCESSORY POWER SUPPLY - .....	72	A
<b>PRECAUTIONS</b> .....	3	Wiring Diagram - ACCESSORY POWER SUPPLY FUSE No. 19 - .....	76	B
Precaution for Supplemental Restraint System (SRS) "AIR BAG" and "SEAT BELT PRE-TENSIONER" .....	3	Wiring Diagram - IGNITION POWER SUPPLY - ....	84	C
Precaution for Procedure without Cowl Top Cover.....	3	Wiring Diagram - IGNITION POWER SUPPLY FUSE No. 3 - .....	101	D
<b>PREPARATION</b> .....	4	Wiring Diagram - IGNITION POWER SUPPLY FUSE No. 4 - .....	110	E
<b>PREPARATION</b> .....	4	Wiring Diagram - IGNITION POWER SUPPLY FUSE No. 44 - .....	113	F
Special Service Tools .....	4	Wiring Diagram - IGNITION POWER SUPPLY FUSE No. 46 - .....	118	G
<b>SYSTEM DESCRIPTION</b> .....	5	<b>OPTION HARNESS</b> .....	126	H
<b>COMPONENT PARTS</b> .....	5	Wiring Diagram .....	126	I
Circuit Breaker .....	5	<b>FUSE BLOCK - JUNCTION BOX (J/B)</b> .....	131	J
Battery .....	5	Fuse, Connector and Terminal Arrangement .....	131	K
Harness Connector .....	5	<b>FUSE, FUSIBLE LINK AND RELAY BOX</b> .....	132	L
Standardized Relay .....	8	Fuse and Fusible Link Arrangement .....	132	
<b>WIRING DIAGRAM</b> .....	11	<b>IPDM E/R (INTELLIGENT POWER DISTRIBUTION MODULE ENGINE ROOM)</b> .....	133	<b>PG</b>
<b>POWER SUPPLY ROUTING CIRCUIT</b> .....	11	Fuse, Connector and Terminal Arrangement .....	133	
Wiring Diagram - BATTERY POWER SUPPLY - ....	11	<b>PCB HARNESS</b> .....	134	N
Wiring Diagram - BATTERY POWER SUPPLY FUSIBLE LINK No. L - .....	27	Connector and Terminal Arrangement .....	134	O
Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 6 - .....	31	<b>HARNESS LAYOUT</b> .....	135	P
Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 7 - .....	37	How To Read Harness Layout .....	135	
Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 9 - .....	39	Outline .....	136	
Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 11 - .....	43	Engine Room Harness .....	137	
Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 34 - .....	46	Engine Control Harness .....	138	
Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 51 - .....	52	Main Harness .....	143	
Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 53 - .....	61	Body Harness .....	144	
		Door Harness .....	146	
		Room Lamp Harness .....	150	
		Tail Harness .....	151	
		<b>BASIC INSPECTION</b> .....	152	

---

<b>BATTERY INSPECTION</b> .....	152	Removal and Installation .....	157
How to Handle Battery .....	152	<b>BATTERY TERMINAL WITH FUSIBLE LINK..</b>	158
Work Flow .....	154	Exploded View .....	158
<b>FUSE INSPECTION</b> .....	155	Removal and Installation .....	158
How To Check .....	155	<b>SERVICE DATA AND SPECIFICATIONS</b>	
<b>FUSIBLE LINK INSPECTION</b> .....	156	<b>(SDS)</b> .....	159
How To Check .....	156	<b>SERVICE DATA AND SPECIFICATIONS</b>	
<b>REMOVAL AND INSTALLATION</b> .....	157	<b>(SDS)</b> .....	159
<b>BATTERY</b> .....	157	Battery .....	159
Exploded View .....	157		

# PRECAUTIONS

< PRECAUTION >

## PRECAUTION

### PRECAUTIONS

#### Precaution for Supplemental Restraint System (SRS) "AIR BAG" and "SEAT BELT PRE-TENSIONER"

INFOID:000000006056696

The Supplemental Restraint System such as "AIR BAG" and "SEAT BELT PRE-TENSIONER", used along with a front seat belt, helps to reduce the risk or severity of injury to the driver and front passenger for certain types of collision. This system includes seat belt switch inputs and dual stage front air bag modules. The SRS system uses the seat belt switches to determine the front air bag deployment, and may only deploy one front air bag, depending on the severity of a collision and whether the front occupants are belted or unbelted. Information necessary to service the system safely is included in the "SRS AIR BAG" and "SEAT BELT" of this Service Manual.

#### **WARNING:**

- To avoid rendering the SRS inoperative, which could increase the risk of personal injury or death in the event of a collision that would result in air bag inflation, all maintenance must be performed by an authorized NISSAN/INFINITI dealer.
- Improper maintenance, including incorrect removal and installation of the SRS, can lead to personal injury caused by unintentional activation of the system. For removal of Spiral Cable and Air Bag Module, see the "SRS AIR BAG".
- Do not use electrical test equipment on any circuit related to the SRS unless instructed to in this Service Manual. SRS wiring harnesses can be identified by yellow and/or orange harnesses or harness connectors.

#### PRECAUTIONS WHEN USING POWER TOOLS (AIR OR ELECTRIC) AND HAMMERS


#### **WARNING:**

- When working near the Air Bag Diagnosis Sensor Unit or other Air Bag System sensors with the ignition ON or engine running, DO NOT use air or electric power tools or strike near the sensor(s) with a hammer. Heavy vibration could activate the sensor(s) and deploy the air bag(s), possibly causing serious injury.
- When using air or electric power tools or hammers, always switch the ignition OFF, disconnect the battery, and wait at least 3 minutes before performing any service.

#### Precaution for Procedure without Cowl Top Cover

INFOID:000000006115718

When performing the procedure after removing cowl top cover, cover the lower end of windshield with urethane, etc.



# PREPARATION

< PREPARATION >

## PREPARATION

### PREPARATION

#### Special Service Tools

INFOID:000000006056697

Tool number (Kent-Moore No.) Tool name	Description
<p>— (J-48087) Battery Service Center</p>  <p>WKIA5280E</p>	<p>Tests battery. For operating instructions, refer to Technical Service Bulletin and Battery Service Center User Guide.</p>

# COMPONENT PARTS

< SYSTEM DESCRIPTION >


## SYSTEM DESCRIPTION

### COMPONENT PARTS

#### Circuit Breaker

INFOID:000000005987069

The PTC thermistor generates heat in response to current flow. The temperature (and resistance) of the thermistor element varies with current flow. Excessive current flow will cause the element's temperature to rise. When the temperature reaches a specified level, the electrical resistance will rise sharply to control the circuit current. Reduced current flow will cause the element to cool. Resistance falls accordingly and normal circuit current flow is allowed to resume.



#### Battery

INFOID:000000005987070

Type		110D26L
20 hour rate capacity	[V – Ah]	12 – 75
Cold cranking current (For reference value)	[A]	720

#### Harness Connector

INFOID:000000005987071

##### HARNESS CONNECTOR (TAB-LOCKING TYPE)

- The tab-locking type connectors help prevent accidental looseness or disconnection.
- The tab-locking type connectors are disconnected by pushing or lifting the locking tab(s). Refer to the figure below.

**CAUTION:**


**Never pull the harness or wires when disconnecting the connector.**

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# COMPONENT PARTS

## < SYSTEM DESCRIPTION >

[Example]



SEL769DA

### HARNESS CONNECTOR (SLIDE-LOCKING TYPE)

- A new style slide-locking type connector is used on certain systems and components, especially those related to OBD.
- The slide-locking type connectors help prevent incomplete locking and accidental looseness or disconnection.
- The slide-locking type connectors are disconnected by pushing or pulling the slider. Refer to the figure below.


#### **CAUTION:**

- **Never pull the harness or wires when disconnecting the connector.**
- **Be careful not to damage the connector support bracket when disconnecting the connector.**

# COMPONENT PARTS

## < SYSTEM DESCRIPTION >

[Example]



### HARNESS CONNECTOR (LEVER LOCKING TYPE)


- Lever locking type harness connectors are used on certain control units and control modules such as ECM, ABS actuator and electric unit (control unit), etc.
- Lever locking type harness connectors are also used on super multiple junction (SMJ) connectors.
- Always confirm the lever is fully locked in place by moving the lever as far as it will go to ensure full connection.

**CAUTION:**

# COMPONENT PARTS

## < SYSTEM DESCRIPTION >

Always confirm the lever is fully released (loosened) before attempting to disconnect or connect these connectors to avoid damage to the connector housing or terminals.




- |                                   |                                  |                  |
|-----------------------------------|----------------------------------|------------------|
| 1. Control unit with single lever | 2. Control unit with dual levers | 3. SMJ connector |
| A. Fasten                         | A. Levers                        | A. Lever         |
| B. Loosen                         | B. Fasten                        | B. Fasten        |
| C. Lever                          | C. Loosen                        | C. Loosen        |

## Standardized Relay

INFOID:000000005987072

### NORMAL OPEN, NORMAL CLOSED AND MIXED TYPE RELAYS

Relays can mainly be divided into three types: normal open, normal closed and mixed type relays.



SEL881H





## TYPE OF STANDARDIZED RELAYS

# COMPONENT PARTS

## < SYSTEM DESCRIPTION >

1M ..... 1 Make  
 1T ..... 1 Transfer

2M ..... 2 Make  
 1M-1B ..... 1 Make 1 Break



SEL882H

A  
 B  
 C  
 D  
 E  
 F  
 G  
 H  
 I  
 J  
 K  
 L  
 N  
 O  
 P

PG

# COMPONENT PARTS

< SYSTEM DESCRIPTION >

Type	Outer view	Circuit	Connector symbol and connection	Case color
IT				BLACK
2M				BROWN
1V+1V				GRAY
1M				RED

The arrangement of terminal numbers on the actual relays may differ from those shown above

SEL188W

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >

## WIRING DIAGRAM

### POWER SUPPLY ROUTING CIRCUIT

Wiring Diagram - BATTERY POWER SUPPLY -

INFOID:000000005987073





A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5589GB  
26101201



# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



JCMWA5591GB


A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
N  
O  
P

PG

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

①  
②  
③  
④  
⑤  
⑥  
⑦  
⑧  
⑨  
⑩  
⑪  
⑫  
⑬  
⑭  
⑮  
⑯  
⑰  
⑱  
⑲  
⑳  
㉑  
㉒  
㉓  
㉔  
㉕  
㉖  
㉗  
㉘  
㉙  
㉚  
㉛  
㉜  
㉝  
㉞  
㉟  
㊱  
㊲  
㊳  
㊴  
㊵  
㊶  
㊷  
㊸  
㊹  
㊺  
㊻  
㊼  
㊽  
㊾  
㊿




JCMWA5592GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >


---

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P



# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



JCMWA5594GB








# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5598GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >






A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5599GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5600GB





# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5604GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - BATTERY POWER SUPPLY FUSIBLE LINK No. L -  
 BATTERY POWER SUPPLY FUSIBLE LINK No. L

INFOID:000000005987074



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L

PG


N  
O  
P

70-169-01

JCMWA5605GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5606GB



# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



JCMWA5608GB


# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 6 -

INFOID:000000005987076

BATTERY POWER SUPPLY FUSE No. 6



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
N  
O  
P


PG

70-169-01

JCMWA5609GB

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5610GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5611GB

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5612GB

# POWER SUPPLY ROUTING CIRCUIT



< WIRING DIAGRAM >

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----




1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

JCMWA5613GB

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5614GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 7 -  
BATTERY POWER SUPPLY FUSE No. 7

INFOID:000000005987077




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

70-169-01

JCMWA5615GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5616GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 9 -  
BATTERY POWER SUPPLY FUSE No. 9

INFOID:000000005987078



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
N  
O  
P


PG

70-169-01

JCMWA5617GB

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5618GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P



# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 11 -  
BATTERY POWER SUPPLY FUSE No. 11

INFOID:000000005987079



A

B

C

D

E

F

G

H

I

J

K

L

**PG**

N

O


P

70-169-01

JCMWA5621GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5622GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P



JCMWA5623GB


# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 34 -

INFOID:000000005987080

BATTERY POWER SUPPLY FUSE No. 34




70-109-01

JCMWA5624GB



# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



JCMWA5626GB








# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

## Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 51 -

INFOID:000000005987081


### BATTERY POWER SUPPLY FUSE No. 51



JCMWA5630GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P


2010.06.03

JCMWA5631GB



# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5633GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



JCMWA5634GB








# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



JCMWA5638GB


# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

## Wiring Diagram - BATTERY POWER SUPPLY FUSE No. 53 -

INFOID:000000005987082


### BATTERY POWER SUPPLY FUSE No. 53



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




2010.06.03

JCMWA5640GB



# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5642GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5643GB

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5644GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5645GB

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5646GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P


JCMWA5647GB



# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
N  
O  
P



JCMWA5649GB


# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - ACCESSORY POWER SUPPLY -

INFOID:000000005987083

ACCESSORY POWER SUPPLY




2010.02.02

JCMWA5650GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5651GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5652GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
N  
O  
P



JCMWA5653GB

PG



# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - ACCESSORY POWER SUPPLY FUSE No. 19 -

INFOID:000000005987084

ACCESSORY POWER SUPPLY FUSE No. 19




70-169-01

JCMWA5654GB



# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5656GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5657GB

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5658GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5659GB

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5660GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P


JCMWA5661GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - IGNITION POWER SUPPLY -


INFOID:000000005987085



JCMWA5662GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
N  
O  
P

PG

JCMWA5663GB








# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5667GB








# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5671GB

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5672GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5673GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5674GB



# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >





# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5678GB



# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



2010.06.03


JCMWA5680GB





# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5683GB



# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5685GB

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5686GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5687GB


# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - IGNITION POWER SUPPLY FUSE No. 4 -  
IGNITION POWER SUPPLY FUSE No. 4

INFOID:000000005987087

Wiring Diagram




70-109-01

JCMWA5688GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5689GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



JCMWA5690GB


# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

Wiring Diagram - IGNITION POWER SUPPLY FUSE No. 44 -

INFOID:000000005987089

IGNITION POWER SUPPLY FUSE No. 44



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
N  
O  
P

PG

70-169-01

JCMWA5691GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----


CAUTION POWER SUPPLY FUSE R1, 44

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----





1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

JCMWA5692GB


# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----



IGNITION POWER SUPPLY FUSE RLY 44




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5693GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



JCMWA5694GB





# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >

## Wiring Diagram - IGNITION POWER SUPPLY FUSE No. 46 -

INFOID:000000005987090

### IGNITION POWER SUPPLY FUSE No. 46




70-169-01

JCMWA5696GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5697GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >




JCMWA5698GB



# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5700GB

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# POWER SUPPLY ROUTING CIRCUIT


< WIRING DIAGRAM >



JCMWA5702GB

# POWER SUPPLY ROUTING CIRCUIT

< WIRING DIAGRAM >



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

JCMWA5703GB


# OPTION HARNESS

< WIRING DIAGRAM >

## OPTION HARNESS

Wiring Diagram

INFOID:000000005987108



OPTION HARNESS


2010.02.02

JCMWA5584GB


# OPTION HARNESS

< WIRING DIAGRAM >

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----




JCMWA5585GB

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# OPTION HARNESS

< WIRING DIAGRAM >




JCMWA5586GB



# OPTION HARNESS

< WIRING DIAGRAM >



JCMWA5588GB



# FUSE BLOCK - JUNCTION BOX (J/B)

< WIRING DIAGRAM >

## FUSE BLOCK - JUNCTION BOX (J/B)

Fuse, Connector and Terminal Arrangement

INFOID:000000005987109



70-169-01

JCMWA5704GB

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P


# FUSE, FUSIBLE LINK AND RELAY BOX

< WIRING DIAGRAM >

## FUSE, FUSIBLE LINK AND RELAY BOX

### Fuse and Fusible Link Arrangement

INFOID:000000005987110



70-169-01

JCMWA5705GB


# IPDM E/R (INTELLIGENT POWER DISTRIBUTION MODULE ENGINE ROOM)

< WIRING DIAGRAM >

## IPDM E/R (INTELLIGENT POWER DISTRIBUTION MODULE ENGINE ROOM)

Fuse, Connector and Terminal Arrangement

INFOID:000000005987111



70-169-01

JCMWA5706GB

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
M  
N  
O  
P

PG


# PCB HARNESS

< WIRING DIAGRAM >

## PCB HARNESS

### Connector and Terminal Arrangement

INFOID:000000006056704



2010.02.02

JCMWA5707GB

# HARNESS LAYOUT


< WIRING DIAGRAM >

## HARNESS LAYOUT

### How To Read Harness Layout

INFOID:000000005987112

- 1 : Connector model
- 2 : Cavity
- 3 : Male (M) and female (F) terminals
- 4 : Connector color
- 5 : Special type



### CONNECTOR SYMBOL

Main symbols of connector (in Harness Layout) are indicated in the below.

Connector type	Male pin type		Star case type	
	Male	Female	Male	Female
Connector symbol				
Ground terminal etc.		-		

JPMIA0114GB

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L

PG


# HARNESS LAYOUT

< WIRING DIAGRAM >

Outline

INFOID:000000005987113

OUTLINE



2013ACE-03

JCMIA0748GB


# HARNESS LAYOUT

< WIRING DIAGRAM >

Engine Room Harness

INFOID:000000005987115

ENGINE COMPARTMENT



ENGINE ROOM HARNESS /  
Engine Compartment

3010 C3-05


JCMIA0749GB

PG

# HARNES LAYOUT

< WIRING DIAGRAM >


PASSENGER COMPARTMENT



# HARNESSES LAYOUT

< WIRING DIAGRAM >

Engine Compartment




A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# HARNES LAYOUT

< WIRING DIAGRAM >

Passenger Compartment



Passenger Compartment (VO37VHR)

56-20-0136


JCMIA0752GB

VK56VD

# HARNES LAYOUT

< WIRING DIAGRAM >

Engine Compartment




JCMIA0753GB

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# HARNES LAYOUT

< WIRING DIAGRAM >

Passenger Compartment



Passenger Compartment (VK56VD)

56-20-0134


JCMIA0754GB

# HARNESS LAYOUT

< WIRING DIAGRAM >

## Main Harness

INFOID:000000005987114



# HARNES LAYOUT


< WIRING DIAGRAM >

Body Harness

INFOID:000000005987117

BODY HARNESS

BODY HARNESS




2010 C30-05

JCMIA0756GB

# HARNES LAYOUT

< WIRING DIAGRAM >  
BODY No. 2 HARNESS



BODY No. 2 HARNESS

5C10C106

JCMIA0757GB

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P




# HARNES LAYOUT

< WIRING DIAGRAM >

FRONT DOOR HARNES (RH SIDE)

FRONT DOOR HARNES (RH SIDE)



50100005

JCMIA0759GB


A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# HARNES LAYOUT

< WIRING DIAGRAM >

REAR DOOR HARNES (LH SIDE)

REAR DOOR HARNES (LH SIDE)



2010/03


JCMIA0760GB

# HARNES LAYOUT

< WIRING DIAGRAM >

REAR DOOR HARNESS (RH SIDE)

REAR DOOR HARNESS (RH SIDE)



5C19C195

JCMIA0761GB


A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# HARNES LAYOUT

< WIRING DIAGRAM >

## Room Lamp Harness

INFOID:000000005987119




JCMIA0762GB

# HARNES LAYOUT

< WIRING DIAGRAM >

## Tail Harness

INFOID:000000005987121



TAIL HARNESS

2010-09-03

JCMIA0763GB

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# BATTERY INSPECTION

< BASIC INSPECTION >

## BASIC INSPECTION

### BATTERY INSPECTION

#### How to Handle Battery

INFOID:000000006056706


#### CAUTION:

- If it becomes necessary to start the engine with a booster battery and jumper cables, use a 12-volt booster battery.
- After connecting battery cables, ensure that they are tightly clamped to battery terminals for good contact.
- Never add distilled water through the hole used to check specific gravity.


#### METHODS OF PREVENTING OVER-DISCHARGE

The following precautions must be taken to prevent over-discharging a battery.


- The battery surface (particularly its top) should always be kept clean and dry.
- The terminal connections should be clean and tight.
- At every routine maintenance, check the electrolyte level. This also applies to batteries designated as "low maintenance" and "maintenance-free".



- When the vehicle is not going to be used over a long period of time, disconnect the battery cable from the negative terminal. (If the vehicle has an extended storage switch, turn it off.)



- Check the charge condition of the battery. Periodically check the specific gravity of the electrolyte. Keep a close check on charge condition to prevent over-discharge.



#### CHECKING ELECTROLYTE LEVEL


#### WARNING:

Never allow battery fluid to come in contact with skin, eyes, fabrics, or painted surfaces. After touching a battery, never touch or rub your eyes until you have thoroughly washed your hands. If acid contacts eyes, skin or clothing, immediately flush with water for 15 minutes and seek medical attention.

# BATTERY INSPECTION

## < BASIC INSPECTION >

- Remove the cell plug using a suitable tool.
- Add distilled water up to the MAX level.




### Sulphation

A battery will be completely discharged if it is left unattended for a long time and the specific gravity will become less than 1.100. This may result in sulphation on the cell plates.


To determine if a battery has been “sulphated”, note its voltage and current when charging it. As shown in the figure, less current and higher voltage are observed in the initial stage of charging sulphated batteries.

A sulphated battery may sometimes be brought back into service by means of a long, slow charge, 12 hours or more, followed by a battery capacity test.



### SPECIFIC GRAVITY CHECK

1. Read hydrometer and thermometer indications at eye level.
2. Use the chart below to correct your hydrometer reading according to electrolyte temperature.



Hydrometer Temperature Correction

Battery electrolyte temperature [°C (°F)]	Add to specific gravity reading
71 (160)	0.032
66 (150)	0.028
60 (140)	0.024
54 (130)	0.020
49 (120)	0.016
43 (110)	0.012
38 (100)	0.008
32 (90)	0.004
27 (80)	0
21 (70)	-0.004
16 (60)	-0.008
10 (50)	-0.012
4 (40)	-0.016
-1 (30)	-0.020
-7 (20)	-0.024

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
N  
O  
P

PG

# BATTERY INSPECTION

## < BASIC INSPECTION >

Battery electrolyte temperature [°C (°F)]	Add to specific gravity reading
-12 (10)	-0.028
-18 (0)	-0.032

Corrected specific gravity	Approximate charge condition
1.260 - 1.280	Fully charged
1.230 - 1.250	3/4 charged
1.200 - 1.220	1/2 charged
1.170 - 1.190	1/4 charged
1.140 - 1.160	Almost discharged
1.110 - 1.130	Completely discharged

## CHARGING THE BATTERY

### CAUTION:

- Never “quick charge” a fully discharged battery.
- Keep the battery away from open flame while it is being charged.
- When connecting the charger, connect the leads first, then turn on the charger. Never turn on the charger first, as this may cause a spark.
- If battery electrolyte temperature rises above 55 °C (131 °F), stop charging. Always charge battery at a temperature below 55 °C (131 °F).

### Charging Rates

Amps	Time
50	1 hour
25	2 hours
10	5 hours
5	10 hours

Do not charge at more than 50 ampere rate.

### NOTE:

The ammeter reading on your battery charger will automatically decrease as the battery charges. This indicates that the voltage of the battery is increasing normally as the state of charge improves. The charging amps indicated above refer to initial charge rate.

- If, after charging, the specific gravity of any two cells varies more than 0.050, the battery should be replaced.

## Work Flow

INFOID:000000006056707

## TROUBLE DIAGNOSIS WITH BATTERY SERVICE CENTER

For battery testing, use Battery Service Center (J-48087). For details and operating instructions, refer to Technical Service Bulletin and/or Battery Service Center User Guide.

# FUSE INSPECTION


< BASIC INSPECTION >

## FUSE INSPECTION

### How To Check

INFOID:000000005987134

- If fuse is blown, be sure to eliminate cause of malfunction before installing new fuse.
- Use fuse of specified rating. Never use fuse of more than specified rating.
- Do not partially install fuse; always insert it into fuse holder properly.
- Remove fuse for "ELECTRICAL PARTS (BAT)" if vehicle is not used for a long period of time.



A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L  
PG  
N  
O  
P

# FUSIBLE LINK INSPECTION


< BASIC INSPECTION >

## FUSIBLE LINK INSPECTION

### How To Check

INFOID:000000005987135

A melted fusible link can be detected either by visual inspection or by feeling with finger tip. If its condition is questionable, use circuit tester or test lamp.



1. Fusible link

### **CAUTION:**

- If fusible link should melt, it is possible that critical circuit (power supply or large current carrying circuit) is shorted. In such a case, carefully check and eliminate cause of malfunction.
- Never wrap outside of fusible link with vinyl tape. Important: Never let fusible link touch any other wiring harness, vinyl or rubber parts.

# BATTERY

< REMOVAL AND INSTALLATION >

## REMOVAL AND INSTALLATION


### BATTERY

#### Exploded View

INFOID:000000005987139

1 : Battery fix frame

Refer to [GI-3, "Contents"](#) for symbols in the figure.



#### Removal and Installation

INFOID:000000005987140

##### REMOVAL

1. Remove battery cover.
2. Remove cowl top cover (RH). Refer to [EXT-21, "Exploded View"](#).
3. Remove cover of battery positive terminal.
4. Loosen battery terminal nuts, and disconnect both battery cables from battery terminals.

**CAUTION:**

**When disconnecting, disconnect the battery cable from the negative terminal first.**

5. Remove battery fix frame mounting nuts and battery fix frame.
6. Remove battery.

##### INSTALLATION

Install in the reverse order of removal.

**CAUTION:**

**When connecting, connect the battery cable to the positive terminal first.**

Reset electronic systems as necessary. Refer to [GI-65, "ADDITIONAL SERVICE WHEN REMOVING BATTERY NEGATIVE TERMINAL : Required Procedure After Battery Disconnection"](#).

A  
B  
C  
D  
E  
F  
G  
H  
I  
J  
K  
L

PG

N  
O  
P

# BATTERY TERMINAL WITH FUSIBLE LINK


< REMOVAL AND INSTALLATION >

## BATTERY TERMINAL WITH FUSIBLE LINK

### Exploded View

INFOID:000000005987141

- 1 : Battery terminal with fusible link
  - 2 : Harness connector
- Refer to [GI-3. "Contents"](#) for symbols in the figure.



### Removal and Installation

INFOID:000000005987142

#### REMOVAL

1. Remove battery cover.
2. Disconnect the battery cable from the negative terminal.
3. Remove cover of battery positive terminal.
4. Remove harness mounting nuts and battery terminal with fusible link mounting nut.
5. Disconnect harness connector and remove battery terminal with fusible link.

#### INSTALLATION

Install in the reverse order of removal.

# SERVICE DATA AND SPECIFICATIONS (SDS)

< SERVICE DATA AND SPECIFICATIONS (SDS)

## SERVICE DATA AND SPECIFICATIONS (SDS)

SERVICE DATA AND SPECIFICATIONS (SDS)

Battery

INFOID:000000005987143

Type		110D26L
20 hour rate capacity	[V – Ah]	12 – 75
Cold cranking current (For reference value)	[A]	720

A

B

C

D

E

F

G

H

I

J

K

L

PG

N

O

P